Amendments to the Claims:

The listing of claims will replace all prior versions, and listings, of claims

in the application:

**Listing of Claims**:

Claim 1. (Currently Amended) Air control system [[in]] for the

front end of a motor vehicle, which front end is defined by a front end wall, and

comprises a bumper unit, (21) and a cooling module, and a motor compartment,

said (22), having openings (28, 31) in a front end wall having air passages (24)

defining the front end (20), through which a cooling air flows into a flow enters

said motor compartment; wherein:

said air control system includes air ducts (2, 3) being provided to

guide which deliver the cooling air flow into the motor compartment,

substantially against [[the]] a direction of travel, said air ducts being and which

are formed by boundary walls (7, 19) disposed approximately parallel to [[the]] a

direction of [[the]] air flow; [[,]]

the boundary walls are (7, 19) being integrated into a body panel

[[(1)]] which extends approximately across the transversely to the direction of air

flow direction and has openings that open to said air ducts and are disposed (6,

10, 11, 18) at least partially in [[the]] an area covered by said air passages; the

Page 3 of 17

## openings (28, 31), characterized in that

the body panel [[(1)]] is fastened mounted to and suspended from the cooling module; [[(22)]] and

the boundary walls (7, 19) projecting project from the marginal perimeter areas adjacent the ports (6, 18) are provided at their free ends with openings, and have circumferential sealing flanges (39, 41, 44) at their free ends.

Claim 2. (Currently Amended) [[Air]] <u>The air</u> control system according to claim 1, characterized in that wherein:

the body panel [[(1)]] is arranged mainly substantially behind the [[a]] bumper unit; and [[(21),]]

the bumper unit (21) comprising comprises a bumper covering.

[[(27),]] a flexural crossbeam [[(25)]] and a bumper interior part. [[(26).]]

Claim 3. (Currently Amended) [[Air]] The air control system according to claim 1, characterized in that 2, wherein one of the openings is a large-area upper opening that is situated [[(6)]] above the flexural beam. [[(25).]]

Claim 4. (Currently Amended) [[Air]] The air control system according to claim 1, characterized in that 2, wherein one of the openings is a large-area lower opening [[(18)]] that is situated beneath the flexural beam. [[(25).]]

- Claim 5. (Currently Amended) [[Air]] The air control system according to claim 3, characterized in that the wherein a lower boundary edge [[(7)]] of the upper opening [[(6)]] of the body panel (1) lies scalingly bears and seals against [[the]] a back side of the flexural beam. [[(25).]]
- Claim 6. (Currently Amended) [[Air]] <u>The air</u> control system according to claim 5, characterized in that wherein:

two circular openings (10, 11) are provided, one on either side of the upper opening; and [[(6),]]

a hollow cylindrical defining wall projects from the marginal areas of which adjoining the marginal areas adjacent the openings a hollow cylindrical defining wall (12, 13) projects perimeter of each of said circular openings.

- Claim 7. (Currently Amended) [[Air]] <u>The air</u> control system according to claim 6, <u>characterized in that wherein</u> two additional circular openings (46, 47) are provided on both sides of the upper opening. [[(6).]]
- Claim 8. (Currently Amended) [[Air]] <u>The</u> control system according to claim 1, <u>characterized in that wherein</u> at least one outside corner area (15, 16) of the body panel [[(1)]] is joined pivotingly to the body panel. [[(1).]]
- Claim 9. (New) An air control system for the front end of a motor vehicle, which front end is defined by a front end wall with air passages therein,

and comprises a bumper unit, a cooling module and a motor compartment, said

air control system comprising:

a body panel that extends substantially transverse to a longitudinal

axis of a body of said vehicle;

a plurality of air ducts which are in communication with openings

in said body panel, said air ducts being configured to guide a flow of air from said

air passages into the motor compartment, and being defined by bounding walls

that are integrated into said body panel; and

mounting means for supporting said body panel in said front end of

the vehicle, said mounting means consisting of mounting eyes in said body panel

by which said body panel is suspended on projections in said cooling unit.

Claim 10. (New) The air control system according to claim 9,

wherein:

the body panel is arranged substantially behind the bumper unit;

and

the bumper unit comprises a bumper covering, a flexural crossbeam

and a bumper interior part.

Page 6 of 17

Claim 11. (New) The air control system according to claim 10, wherein one of the openings is a large-area upper opening that is situated above the flexural beam.

Claim 12. (New) The air control system according to claim 10, wherein one of the openings is a large-area lower opening that is situated beneath the flexural beam.

Claim 13. (New) The air control system according to claim 11, wherein a lower boundary edge of the upper opening of the body panel bears and seals against a back side of the flexural beam.

Claim 14. (New) The air control system according to claim 13, wherein:

two circular openings are provided, one on either side of the upper opening; and

a hollow cylindrical defining wall projects from the perimeter of each of said circular openings.

Claim 15. (New) The air control system according to claim 14, wherein two additional circular openings are provided on both sides of the upper opening.

Serial No. 10/530,766 Amendment Dated: Reply to Office Action Mailed: November 25, 2008 Attorney Docket No. 095309.56086US

Claim 16. (New) The control system according to claim 9, wherein at least one outside corner area of the body panel is joined pivotably to the body panel.